

WHEN TO PERFORM

SERVICES

By Wessler Engineering

WHEN TO PERFURIN

WET WEATHER INSPECTIONS

are best when performed before a heavy rainfall begins. You should start as close to the WWTP as possible and work your way out to the system, once heavy clear flow is observed, then the study area can be narrowed.

Should be performed when groundwater is at its highest. Surface water enters the sewer through the manhole causing it to deteriorate and collapse.



NIGHT FLOW ISOLATION

Can be performed throughout the year, but the best results are seen after a steady 2 - 3 inch rain event and between the hours of 1 and 5 a.m.



SUMP PUMP INSPECTIONS

There is no 'best' time of year for sump pump inspections; it is best to send out resident evaluations then target a specific neighborhood or area, usually older sections.



POLE CAM INVESTIGATIONS

allow you to quickly inspect your sanitary and storm sewer systems to identify structural and maintenance issues, and assist you in identifying which sewers should receive closed-circuit televising and cleaning.

SMOKE TESTING is one of the quickest and most cost-effective ways for a community to find leaks their sanitary sewer system. Non-toxic smoke is blown through isolated pipe segments in the sanitary sewer system to observe both private and public property defects.



CHEAT

Know when to inspect your sanitary sewers! Use this guide to gather the best results possible.

Pole Cam Investigation Night Flow Isolation												
CCTV Sump Pump Inspection												
Wet Weather Inspection												
	JANUARY	FEBRUARY	MARCH	APRIL	MAY	JUNE	JULY	AUGUST	EPTEMBER	OCTOBER	NOVEMBER	DECEMBER