



**The highest  
quality ALD  
systems for  
demanding  
applications.**

## **PICOSUN™ R-200 STANDARD**

**The PICOSUN™ R-200 Standard ALD systems are suitable for R&D on dozens of applications such as IC components, MEMS devices, displays, LEDs, lasers, and 3D objects such as lenses, optics, jewelry, coins, and medical implants.**

The PICOSUN™ R-200 Standard ALD system is the market leader in thermal ALD research tools. It has become the tool of choice both for companies and research institutes driven by innovation.

The agile design enables the highest quality ALD film depositions together with the ultimate flexibility of the system to fit future needs and applications. The patented hot-wall design with fully separate inlets and instrumentation enables particle-free processing adaptable on a wide range of materials on wafers, 3D objects, and all nanoscale features. Excellent uniformity even on the most challenging through-porous, ultra-high aspect ratio, and nanoparticle samples can be achieved thanks to our proprietary Picoflow™ technology. The PICOSUN™ R-200 Standard systems are equipped with highly functional and easily exchangeable precursor sources for liquid, gaseous, and solid chemicals. Integration with glove boxes, powder chambers, and various in situ analytics systems enable efficient and flexible research with good results, no matter what your research area is now, or what it might become later on.

### **TECHNICAL FEATURES**

#### **Typical substrate size and type**

- 50-200 mm single wafers
- 156 mm x 156 mm solar Si wafers
- 3D objects
- Powders and particles
- Mini-batch
- Porous, through-porous, and high aspect ratio (up to 1:2500)

#### **Processing temperature**

- 50 – 500°C

#### **Typical processes**

- $\text{Al}_2\text{O}_3$ ,  $\text{TiO}_2$ ,  $\text{SiO}_2$ ,  $\text{Ta}_2\text{O}_5$ ,  $\text{HfO}_2$ ,  $\text{ZnO}$ ,  $\text{ZrO}_2$ ,  $\text{TiN}$ ,  $\text{AlN}$ , metals such as Pt or Ir

#### **Substrate loading**


- Manual loading with a pneumatic lift
- Load lock with magnetic manipulator arm

#### **Precursors**

- Liquid, solid, gas, ozone
- Up to 6 sources with 4 separate inlets

#### **Options**

- Picoflow™ diffusion enhancer, RGA,  $\text{N}_2$  generator, gas scrubber, customized designs, glove box compatibility for inert loading



# THE PRINCIPLE OF ALD



Introduction of molecules  
containing element A.



Adsorption of the molecules  
on the surface.



Introduction of molecules  
containing element B and  
reaction with element A on the  
surface.



Completion of one monolayer  
of compound AB.

Repeat cycle till desired film  
thickness is reached.

**picosun**

## PICOSUN HQ

Email: [info@picosun.com](mailto:info@picosun.com)

Tel. +358 50 321 1955

### Picosun Oy

Tietotie 3

FI-02150 Espoo, Finland

### Picosun Oy (factories)

Masalantie 365

FI-02430 Masala, Finland

## PICOSUN BRANCH OFFICES

Email: [sales@picosun.com](mailto:sales@picosun.com)

### Picosun Europe

Tel. +49 1522 449 49 11 (Germany)

Tel. +33 60 785 1176 (France)

### Picosun USA

Tel. +1 214 790 0844

### Picosun Asia, Singapore

Tel. +65 9830 1709

### Picosun Taiwan

Tel. +886 90 515 2985

### Picosun China

Tel. +86 139 2640 6106

### Picosun Japan

Tel. +81 3 6431 9500

### Picosun Korea

Tel. +82 10 3493 7831

### Picosun India

Tel. +91 96000 28593

This technology is protected via  
granted patents or is the subject of  
pending patent applications.

PICOSUN™ R-200 Standard • Version 09\_2021