

ENERGY ADVANTAGE™

MULTI-LOAD SOFT-MOUNT WASHERS

MXS20PD, MXS25PD, MXS30PD, MXS40PD, MXS55PD, MXS65PD

COIN MARKET

Introducing the new Maytag Commercial Laundry Energy Advantage™ Multi-Load Soft-Mount Washers, the next generation of multi-load washers built for the demands of today and tomorrow.



Revenue-Generating Controls

- 48 revenue-generating wash cycle options increase profitability
- Multiple language options



MAYTAG connect 360° Compatible

- Receive maintenance alerts, change pricing, track revenue wirelessly, and more
- Customers can receive a text when machine is available or their laundry is complete



Faster Spin

- 400 G spin speed extracts more water resulting in faster dry times



Better Energy and Cleaning Performance

- TurboWash™ System spray baffles and tumble patterns provide optimal water savings and cleaning



USB Programmability

- Easy uploads and downloads of machine settings and software



New Door Design

- Larger door opening and 180-degree door swing allows for easier loading and unloading
- Oversized ergonomic door knob for easy opening
- Durable integrated door hinges



Model MXS40PD shown.



Visit maytagcommerciallaundry.com




WHAT'S INSIDE MATTERS™

MY140247 8/14

ENERGY ADVANTAGE™ MULTI-LOAD SOFT-MOUNT WASHERS

MXS20PD, MXS25PD, MXS30PD, MXS40PD, MXS55PD, MXS65PD

COIN MARKET

WASHER SPECIFICATIONS						
MODEL	MXS20PDATS	MXS25PDATS	MXS30PDATS	MXS40PDATS	MXS55PDATS	MXS65PDATS
MOTOR						
Inverter Drive	Yes	Yes	Yes	Yes	Yes	Yes
Variable Speed	Yes	Yes	Yes	Yes	Yes	Yes
HP (kw)	1.0 (0.75)	1.5 (1.1)	2.0 (1.5)	3.0 (2.2)	4.0 (3.0)	4.0 (3.0)
Voltage	208–240V Single-Phase or Three-Phase	208–240V Single-Phase or Three-Phase	208–240V Single-Phase or Three-Phase	208–240V Single-Phase or Three-Phase	208–240V Single-Phase or Three-Phase	208–240V Single-Phase or Three-Phase
BREAKER SIZE—AMPS	15A	15A	20A	20A	20A	20A
SPEED						
Extract Speed—Max rpm	1165	1075	1075	980	980	915
Extract Speed—Max g-force	400	400	400	400	400	350
LIQUID SOAP SIGNALS	Yes	Yes	Yes	Yes	Yes	Yes
CONTROLS	Rev-Gen	Rev-Gen	Rev-Gen	Rev-Gen	Rev-Gen	Rev-Gen
CONNECTIVITY	Connect 360™ Compatible	Connect 360° Compatible	Connect 360° Compatible	Connect 360° Compatible	Connect 360° Compatible	Connect 360° Compatible
USB PROGRAMMABILITY	Yes	Yes	Yes	Yes	Yes	Yes
WATER INLET/HOSE						
Water Inlet—in.	BSP 3/4	BSP 3/4	BSP 3/4	BSP 3/4	BSP 3/4	BSP 3/4
Operating Pressure—psi /bar	14.5–116/1–8	14.5–116/1–8	14.5–116/1–8	14.5–116/1–8	14.5–116/1–8	14.5–116/1–8
Drain Size Diameter—in. (mm)	3 (76)	3 (76)	3 (76)	3 (76)	3 (76)	3 (76)
CAPACITY						
Lbs. (kg)	20 (9)	25 (11)	30 (14)	40 (18)	55 (24)	65 (28)
Cylinder Volume—cu. ft. (liters)	2.65 (75)	3.71 (105)	4.77 (135)	6.36 (180)	8.48 (240)	9.89 (280)
Cylinder Diameter—in. (mm)	20.87 (530)	24.4 (620)	24.4 (620)	29.53 (750)	29.53 (750)	29.53 (750)
Cylinder Depth—in. (mm)	13.39 (340)	13.71 (348)	17.63 (448)	16.05 (408)	21.40 (544)	24.95 (634)
COLOR						
Front Panel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Side Panels	Dark Gray	Dark Gray	Dark Gray	Dark Gray	Dark Gray	Dark Gray
APPROXIMATE WEIGHT						
Crated—lbs. (kg)	441 (200)	518 (235)	606 (275)	871 (395)	992 (450)	1135 (515)
Uncrated—lbs. (kg)	408 (185)	463 (210)	563 (255)	838 (380)	948 (430)	1092 (495)
DIMENSIONS						
Height—in. (mm)	44.83 (1139)	49.16 (1249)	49.16 (1249)	56.45 (1434)	56.45 (1434)	56.45 (1434)
Width—in. (mm)	27.95 (710)	31.29 (795)	31.29 (795)	38.18 (970)	38.18 (970)	38.18 (970)
Depth Including Handle and Vent on Back—in. (mm)	31.10 (790)	31.29 (795)	37.20 (945)	38.18 (970)	43.50 (1105)	46.65 (1185)
Floor to Bottom of Door—in. (mm)	13.74 (349)	13.46 (342)	13.46 (342)	18.77 (477)	18.77 (477)	18.77 (477)
Floor to Drain Outlet Center—in. (mm)	3.46 (88)	3.46 (88)	3.46 (88)	4.27 (109)	4.27 (109)	4.27 (109)
Side to Drain Outlet Center—in. (mm)	9.05 (230)	9.05 (230)	9.05 (230)	10.62 (270)	10.62 (270)	10.62 (270)
Door Opening Diameter—in. (mm)	12.99 (330)	16.14 (410)	16.14 (410)	18.11 (460)	18.11 (460)	18.11 (460)

See specific instructions for proper installation.



Five-Year Limited Warranty on Parts (Parts Only—Labor Not Included). For the first five years from the original date of purchase, when this commercial appliance is installed, operated and maintained according to the instructions attached to or furnished with the product, Maytag brand of Whirlpool Corporation (hereafter “Maytag”) will pay for factory-specified replacement parts to correct defects in materials or workmanship that existed when this commercial appliance was purchased. This limited warranty does not include labor.

Sixth- Through Tenth-Year Limited Warranty (Certain Component Parts Only). In the sixth through tenth years from the date of original purchase, when this commercial appliance is installed, operated, and maintained according to instructions attached to or furnished with the product, Maytag will pay for factory-specified replacement parts for the following components to correct non-cosmetic defects in materials or workmanship in the part that prevent function of the product and that existed when this commercial appliance was purchased. This is a limited 10-year warranty on the named parts only and does not include labor: outer shell, drum and shaft assembly, inner welded frame and bearings and seals. See complete warranty for details.