## **SWARCO**

# McCAIN 332/334 CCTV EQUIPMENT CABINET



SWARCO McCain Inc.'s 332/334 CCTV Equipment Cabinet is an industry standard 170/2070 style cabinet ideal for accommodating all your communications requirements. The quality materials used and its rugged construction make it an excellent cabinet when dependable and low-maintenance installation is required. Its 19-inch Electronics Industry Alliance (EIA) rack and modular design allow for the easy installation and interchange of standard assemblies and components. The cabinet meets all the Caltrans requirements including TEES, TSCES, and FHWA.



View from back of cabinet shown

## **KEY BENEFITS**

- Provides dependability with rugged construction
- Allows easy access to the cabinet's large interior through the double doors
- Provides maximum security using 3-point latching system with industry standard locks
- Reduces the effects of vandalism with anti-graffiti coating
- Assure interchangeability between manufacturers with standard assemblies

## PRODUCT DESCRIPTION

The McCain 332/334 CCTV Equipment Cabinet is designed to house 170 or 2070 controllers as well as equipment necessary for CCTV and communications requirements. This robust cabinet is constructed from marine-grade aluminum and is accessed via a front and back door making it durable and easily maintained. The cabinet comes equipped with an industry standard 19-inch EIA rack.


The standard cabinet offers a service panel with four circuit breakers: Main, Clean Power, Raw Power, and an Equipment Circuit. Also included is a fluorescent lamp controlled by a door switch and a thermostat-controlled exhaust fan.

The cabinet is secured via a 3-point latching system and protected with a padlock providing secure installations and easy access for maintenance.




# McCAIN 332/334 CCTV EQUIPMENT CABINET


FRONT



SIDE



воттом



## STANDARD FEATURES

- EIA 19" rack
- · Fluorescent light, door switch
- Shelves (2)

## ASSEMBLIES AND COMPONENTS

- · Main circuit breaker, 30A
- · Raw power circuit breaker, 15A
- · Clean power circuit breaker, 15A
- · Equipment circuit breaker, 15A
- Duplex receptacles (2), raw power circuit
- Duplex receptacles (2), clean power circuit
- · GFI duplex receptacle, equipment circuit

## **GENERAL SPECIFICATIONS**

Dimensions <sup>1</sup> :	24"W x 67"H x 30"D
Material:	5052-H32 aluminum, 0.125" thick
Finishes <sup>2</sup> :	Natural, anodized, powder coated
Door:	Front door (1), back door (1), both full size
Latching System:	3-point, choice of Corbin or Best locks
Handles:	3/4" round, stainless steel with padlock feature
Door Stops:	90° (±10°), each door, top 90° and 180° (±10°), each door, bottom
Rack Assembly:	Removable 19" EIA rack
Ventilation:	Thermostatically controlled 100 CFM fan, louvered air intake in door, pleated filter
Mounting:	Base mounted
Shipping Weight <sup>3</sup> :	192 lbs

## **OPTIONS**

- 3/4" x 16" anchor bolts for mounting (4)
- · Sun shields
- Drawer assembly(s)
- · Connection and termination panels



<sup>&</sup>lt;sup>1</sup>Dimensions rounded to the nearest inch

<sup>&</sup>lt;sup>2</sup>Powder coated options include standard, anti-graffiti, and custom colors

<sup>&</sup>lt;sup>3</sup>Without plug-ins or controllers