

SWARCO

McCain GPS TIME SOURCE MODULES

STAND ALONE 2070 PLUG-IN (2070-7G)

The McCain GPS Time Source Modules are easy-to-use, microprocessor-based Universal Time Base (UTB) devices that provide accurate time-of-day information for traffic signal controllers. The McCain GPS Time Source retrieves time signals from the atomic clocks of the United States National Institute of Standards (NIST) broadcast on the GPS (Global Positioning System) satellite network. Using a precision GPS receiver and microprocessor, the module decodes time signals and interfaces with the traffic control equipment.



Stand-Alone
(General Purpose & NEMA)



2070 Version
(2070-7G)

KEY BENEFITS

- Synchronizes time-of-day to GPS
- Updates daylight savings and leap second time corrections automatically
- Meets Caltrans requirements for global positioning latitude and longitude

PRODUCT DESCRIPTION

McCain GPS Time Source Modules consist of a GPS receiver with an antenna and a microprocessor controlled circuit. Units read raw GPS time data, accept user commands, output serial data streams, and perform other processing tasks.

Time and date functions are automatic with no jumpers or switches to set. User defined parameters are stored in internal FLASH.

Commands can then be sent to the GPS Time Source Module from the controller or from a PC. All modules have an easy-to-use Windows-based configuration software.


The 2070-7G, the 2070 version module, can also be programmed directly from the 2070 controller with an optional easy-to-use OS-9 configuration software.

The Stand-Alone GPS Time Source Module is a specialized UTB for general purpose and NEMA controllers. In NEMA controllers the Stand-Alone version provides a one-second pulse at a specific time of day, which is user configurable.

McCain GPS TIME SOURCE MODULES


STAND ALONE

TOP




2070-7G not shown

SIDE



ANTENNA



4" BNC Connector
(Stand-Alone)

GPS Utility (optional)



16" SMA Connector
(2070-7G Version)

STANDARD FEATURES

GPS Antenna

- Small exterior antenna with versatile mounting options
- Coaxial cable with BNC adapter¹ or SMA connector²
- Mounting hardware: flat washer, lock washer, and nut
- Gasket attached to underside of antenna housing
- Query ("Q") and Set ("S") commands
- User set parameters in internal FLASH
- Stand-Alone housing is designed for mounting indoors or in a weatherproof cabinet

Installation

- Stand-Alone: Mounts directly to any surface with use of mounting flanges (2)
- 2070-7G: Controller's communication slot

INTERFACES

Communication Interfaces

- Stand-Alone: RS232
- 2070-7G: RS485³

SOFTWARE (OPTIONAL)

- An optional easy-to use Windows-based configuration software for all GPS Time Source Modules is available upon request.
- An OS-9 based configuration GPS Utility is available for the 2070 version upon request.

GENERAL SPECIFICATIONS

	STAND ALONE	2070-7G
Dimensions ⁴ :	3.5"W x 1.5"H x 6"L EIA rack mount form factor (plug-ins) Meets dimensions for 2070 2x modem cards	Meets dimensions for 2070 2x modem cards
Power:	+5 VDC to +36 VDC (5 VDC @ 80mA)	+5 VDC @ 80mA
Environment:	Operating Temperature: -40° C to +85° C Humidity: 0 to 95% (non condensing)	Operating Temperature: -40° C to +85° C Humidity: 0 to 95% (non condensing)

OPTIONS

- PC configuration and power/data communication cable for Stand-Alone version
- Data NEMA communication cable for Stand-Alone version
- PC configuration cable for 2070-7G

¹Stand-Alone

²2070-7G

³Dimensions rounded to the nearest half inch

⁴Uses one 2070 modem channel, second channel brought out to front panel