

Restek GC Accessories

Available from:
LECO Australia Pty Ltd
PO Box 6006, Baulkham Hills BC NSW 2153
Ph: +61 (0) 2 9849 5900 Fx: +61 (0) 2 9894 5247
Ben MacLeod - Sales Engineer - Separation Science
Email: ben_macleod@leco.com

Dynamic Duo

Restek's Leak Detector and ProFLOW 6000 Flowmeter

An Unbeatable Combination



RESTEK

Pure Chromatography

www.restek.com

Restek's Dynamic Duo

Prevent Small Leaks from Causing Big Problems with a Restek Leak Detector

Taking a few minutes to ensure all critical seals in the GC system are leak free prevents costly downtime, waste, and damage. Restek's new electronic leak detector lets you pinpoint small gas leaks quickly and accurately before they cause bigger problems.

Detect a Wide Range of Lab Gases

Easily find leaks for a broad range of common lab gases with confidence. Restek's leak detector helps you locate even low-level leaks of helium, nitrogen, argon, carbon dioxide, and hydrogen.

Ready When You Are

No more waiting for a full charge—unit can be operated during charging or used up to 12 hours between charges.

Flexible Charging Options

New charging kit includes both a USB charging cable and a universal AC power adaptor (U.S., UK, Europe, Australia, Japan) so you can charge anywhere, anytime.

Easy Sampling

Optimized internal flow sweeps the sample path clean, permitting more sensitive detection.

Audible Feedback

You can determine the severity of a leak with an audible tone; no need to look away from the probe to check the LED display.



An Unbeatable Combination!

Order today at www.restek.com/dynamic-duo

ProFLOW 6000 Flowmeter

With its wide range of capabilities, the ProFLOW 6000 flowmeter simplifies gas flow measurement in the lab. Real-time measurements can be made for various types of flow paths, including continually changing gas types.

Ease of Use

Ergonomic design and side grips ensure comfortable handheld use; extendable stand makes conversion to benchtop use quick and easy.

NIST-Traceable Calibration

You can rely on accurate calibration over the entire range of measurable flow rates. Recalibration service is also available to support preventative maintenance programs.



Accurate Measurements

More accurate than a bubble flowmeter, the ProFLOW 6000 flowmeter is accurate to $\pm 2\%$ of the flow reading or ± 0.2 mL/min, whichever is greater.

Volumetric Flowmeter

Measure the flow rate of any gas, including gas mixtures. Unlike mass flowmeters, this volumetric unit is not limited to a preset list of gases.

Extended Flow Range

Offering a wide range of flow rates, the ProFLOW 6000 flowmeter accurately measures flows from 0.5 mL/min to 500 mL/min.

Dynamic Duo (Restek Leak Detector and ProFLOW 6000 Flowmeter)

Protect your instrument and improve data quality with this powerful pair from Restek. Checking for leaks and verifying flows before you start running help you avoid costly problems later.

| Description | Certification | qty. | cat.# |
|---|------------------------------------|------|-------|
| Dynamic Duo Combo Pack (Restek Leak Detector and ProFLOW 6000 Flowmeter) | TBD | kit | 22654 |
| Related Products and Accessories | | | |
| Leak Detector (includes: carrying case, universal AC power adaptor [U.S., UK, Europe, Australia, Japan], 6-ft USB charging cable) | TBD | ea. | 28500 |
| Small Probe Adaptor for Leak Detector | | ea. | 22658 |
| Restek ProFLOW 6000 Electronic Flowmeter with Hard-Sided Carrying Case | CE, Ex, WEEE, RoHS 2, China RoHS 2 | ea. | 22656 |
| Soft-Sided Storage Case for Leak Detector or ProFLOW 6000 Flowmeter | | ea. | 22657 |
| Charging Kit (includes: 6-ft USB charging cable and universal AC power adaptor [U.S., UK, Europe, Australia, Japan]) | | kit | 28502 |
| 6-ft USB charging cable | | ea. | 28501 |

Restek's New Leak Detector

Redesigned and better than ever, our new leak detector is an essential tool for troubleshooting and routine maintenance of your gas chromatograph. Don't risk damaging your system or losing sensitivity; check for leaks often and protect your GC column and instrument with a Restek leak detector!



Leak Detector Specifications

Detectable Gases: Helium, nitrogen, argon, carbon dioxide, hydrogen*

Battery: Rechargeable nickel-metal hydride (NiMH) internal battery pack (12 hours normal operation)

Ambient Temperature: 50–98.6 °F (10–37 °C)

Humidity Range: 0–97%

Warranty: One year

Certifications: CE (EU, Korea, Japan, Australia)

Compliance: WEEE, CEC, China RoHS 2

Indoor Use Only

Limits of Detection

These gases can be detected with the Restek electronic leak detector at the following leak rates:

Minimum Detectable Gas Limits and Indicating LED Color:

Helium, 1.0×10^{-5} , red LED

Hydrogen*, 1.0×10^{-5} , red LED

Nitrogen, 1.4×10^{-3} , yellow LED

Argon, 1.0×10^{-4} , yellow LED

Carbon dioxide, 1.0×10^{-4} , yellow LED

Gas detection limits measured in atm cc/sec.

Avoid using liquid leak detectors on a GC! Liquids can be drawn into the system and/or into the leak detector.

*Caution: The Restek electronic leak detector should only be used to detect trace amounts of hydrogen in a noncombustible environment. It is NOT designed for determining leaks in a combustible environment. A combustible gas detector should be used for determining combustible gas leaks under any condition. When using it to detect hydrogen, the Restek electronic leak detector may only be used for determining trace amounts in a GC environment.

ProFLOW 6000 Flowmeter

With its wide range of capabilities, the ProFLOW 6000 flowmeter simplifies gas flow measurement in the lab. Real-time measurements can be made for various types of flow paths, including continually changing gas types.

Flowmeter Specifications:

Type of Flowmeter: Volumetric

Battery: 2-AA

Operating Temp. Range: 32–120 °F (0–48 °C)

Warranty: One-year warranty (excludes recalibration)

Certifications: CE, Ex

Compliance: WEEE, RoHS 2, China RoHS 2

Patented



Optional Accessories



22657

Soft-Side Carry/Storage Case
Ideal for storing your leak detector or flowmeter in smaller spaces such as a tool box.



22658

Small Probe Adaptor for Leak Detector
Verify hard-to-reach leaks using the small probe adaptor.

Order today at www.restek.com

RESTEK
Pure Chromatography

Questions? Contact us or your local Restek representative (www.restek.com/contact-us).

Restek patents and trademarks are the property of Restek Corporation. (See www.restek.com/Patents-Trademarks for full list.) Other trademarks in Restek literature or on its website are the property of their respective owners. Restek registered trademarks are registered in the U.S. and may also be registered in other countries. To unsubscribe from future Restek communications or to update your preferences, visit www.restek.com/subscribe. To update your status with an authorized Restek distributor or instrument channel partner, please contact them directly.

© 2019 Restek Corporation. All rights reserved. Printed in the U.S.A.

www.restek.com



Lit. Cat.# GNSS1769B-UNV