PeoplePoint™ Premium





The PeoplePoint™ Premium time clock delivers the flexibility your customers' need

Accu-Time Systems' Android-based PeoplePoint Premium offers a new level of interaction for employee self-service applications. Designed with data security in mind, the 10.1" widescreen touch display makes it easy to navigate schedules, view accruals, and enforce attestation.

As a Value Added Reseller you can now develop Workforce Management technology and employee self-service applications that can be easily developed and deployed on the Android-based PeoplePoint Premium.

PeoplePoint™ Premium features

OS Linux or Android

- 10.1" Widescreen Touch Display
- 2 Speakers
- Wide Angle Camera.
- Microphone
- High-Performance Processor
- eMMC 16GB Storage
- Programming Languages Include: Java, Python, Android, HTML5

To learn more about ATS and Premium, visit www.accu-time.com or call -1 860.870.5000





PeoplePoint™ Premium Terminal Specifications

Display

• 10.1" TFT Capacitive Touch, 1280 x 800 Resolution

Processor

• Freescale iMX6 - Quad Core up to 1GHz

Clock

Battery-backed real-time clock, 12- or 24-hour format (quartz precision)

Keypad

- 20-key tactile 4x5 matrix

» Numeric keypad 0-9

» Eight software-defined function keys

» Keys, Clear/Enter keys

Customizable overlay with your brand on the terminal

Memory

2GB DDR3 RAM

512MB NAND FLASH

• Non-removable eMMC

Mass Storage

• 16GB, of which at least 10GB are user available

Programming

Linux with Java™/Python, web services / HTML

Android-based with Android Studio, web services HTML5.

Application Software

 ATS AccuCollect - Configurable punch workflows and back-end communication interface (on Linux)

Platform Os

• Linux® or Android-based

Diagnostics

On-board and remote diagnostics capability

Interface

Standard 10/100/1000 BASE-T Ethernet

Optional internal 4G cellular modem (On Linux OS)

Internal USB port

Optional 4-port USB hub

Enclosure

PC/ABS

Power

• 12 VDC (nominal) 2A, 24W maximum

• Optional uninterruptible power supply

Optional IEEE 802.3/at-compliant POE module

Environment

• Operation Temperature: 0° to 50°C (32° to 122°F)

Dimensions

H 32.4CM X W 30.73CM X D 10.16CM (H 12.75" X W 12.1" X D 4")

Certifications

CE Mark, FCC Part 15 Class A

Accessories

Biometric readers – 1:1 and 1:n

• Integrated visible or infrared barcode readers

• Integrated magnetic stripe readers

Smartcard readers – contactless (HID® ProxPoint®, HID iCLASS®,

Mifare™, Marin)

Optional external reader - Wiegand compatible

• Dry-contact relay modules (Dual Form C, 48V/2A)

ACCU-TIME SYSTEMS INC.

THE AMERICAS

Corporate Headquarters

20-B International Drive

Windsor, CT 06095

TEL: (860) 870-5000

FAX: (860) 872-1511

Toll Free: (800) 355-4648 sales@accu-time.com

www.accu-time.com

EMEA & APAC

United Kingdom

TEL: +44 (0) 1202 606068

All Other Locations

TEL: +44 (0) 2920 885599

