

# 714E Series

# **Technical Data Sheet**

# PRODUCT DESCRIPTION

A versatile and quick-dry low-HAPS, low-VOC high-gloss finish designed for interior or exterior exposure. Products in this line are less than 3.5 lbs/gallon VOC. Should be used over an industrial primer.

# PRODUCT AND PERFORMANCE DATA

#### **Product Data**

Property	Result
Volume solids (%)	31 ± 2
Weight solids (%)	38 ± 2
VOC	413.91 g/l 3.45 lb/gal
HAPS	Less than 1%
Theoretical Coverage (1.0 mil)	497.2 ft²/gal
Recommended dry film thickness	1.5 – 3.0 mils
Dry to Handle	60 minutes

\*All above testing and data gathered from fully cured 714E200, Black

#### SURFACE PREPARATION

#### **Pre-cleaning:**

Clean all surfaces to be coated in accordance with SSPC-SP-1, Solvent Cleaning prior to additional surface preparation or coating application. Surface must be clean, dry and free of any dirt, dust, oil, and all other visible contaminates.

# **Surface Preparation**

Recommended	SSPC SP 6 (Commercial Blast Cleaning)
Minimum	SSPC SP 2 or SP 3 (Hand or Power Tool Cleaning)

Suitable Primers: For metal - Forrest's 716P (designed for use with 714E) 16P, 26P, or 216P

#### MIXING AND THINNING

#### **Mix Directions**

Stir thoroughly before and occasionally during use.

#### **Thinning Directions**

Product packaged ready to apply. If needed thin up to 10% maximum with 81T714, Low HAPS Thinner.

This Technical Data Sheet supersedes those previously issued. <u>www.forrestpaint.com</u> <u>info@forrestpaint.com</u>



# 714E Series

APPLICATION

# **Application Parameters**

Relative Humidity	< 80%
Minimum Temperature	40°F
Maximum Temperature	100°F

\*The application temperature should be at minimum 5°F above the dew point.

# **Application methods**

The product can be applied by:

#### Spray

Airless spray: 0.011" - 0.017"

Conventional spray: 0.8mm - 1.8mm

**Brush/Roll:** Recommended for stripe coating and small areas. Care must be taken to achieve the specified dry film thickness.

# STORAGE

The product must be stored in accordance with local and national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 73°F (23 °C) = minimum of 12 months \* \*When kept in recommended storage condition and original unopened containers.

# CAUTION

Adequate health and safety precautions should be observed during storage, handling, use and curing periods. **READ SAFETY DATA SHEETS BEFORE USING THIS PRODUCT** 

# DISCLAIMER

The technical data and suggestions for use in this product data sheet are currently correct to the best of our knowledge, but are subject to change without notice. Because application and conditions vary, and are beyond our control, we are not responsible for results obtained in using this product, even when used as suggested. The user should conduct tests to determine the suitability of the product for the intended use under then existing conditions. Our liability for breach of warranty, strict liability in tort, negligence or otherwise is limited exclusively to replacement of the product or refund of its price. Under no circumstances are we liable for incidental or consequential damages.