ROOFTOP ATTACHMENT



FiberTite U-AnchorTM **U2400-FTR**

Product Data

FiberTite U-Anchor™ products are lightweight rooftop attachments designed to provide a positive and watertight attachment for mechanically attached and adhered FiberTite Roof Systems.

DESCRIPTION

The U2400-FTR is a lightweight rooftop attachment system consisting of a U-Anchor 2000 Series plate and FiberTite target membrane. The target membrane is factory sealed to the top of the plate. The U2400- FTR provides a positive and watertight attachment for mechanically attached and adhered FiberTite Roof Systems.

APPLICATIONS

- Pipe & Wire Management
- **Bracing & Support**
- **Heavy Equipment**

U-ANCHOR ATTACHMENT

The U2400-FTR is attached by fastening through the roofing assembly into the structural decking with 2-8 approved fasteners. The target membrane is then hot air welded around the perimeter to the roof membrane.

Fastener selection is dictated by the system assembly, deck type, and the project engineer.

Refer to installation instructions before installing.

EQUIPMENT ATTACHMENT

To securely mount your rooftop equipment to the FiberTite U-Anchor, after its installed, the connection nut must be fastened to approximately 20-25 torque pounds.

Use a calibrated torque wrench during install to ensure appropriate results are achieved.

TESTING / APPROVALS

LARR Listed

RATINGS

Results are based on plate performance only.

- Ultimate Load Shear: 4,000 lbs
- Ultimate Load Tension: 3.000 lbs

Tested in accordance with ICC-ES AC467 Section 3.2





These specifications are current as of the date of printing. Revisions or additions may be issued periodically. For a listing, presentation, and download of the most recent data, visit:

www.FiberTite.com/document-library/product-data-sheets

PHYSICAL PROPERTIES

Bolt - Attachment nut not included		
Bolt Size	3/8"-16 x 1.5" *	
Material	304 Stainless Steel	
Plate		
Outer Diameter	5-1/2"	

· · · · · ·		
Outer Diameter	5-1/2"	
Fastener Hole Diameter	17/64" (8 holes)	
Fastener Hole Pattern	4-1/8" Diameter	
Material Thickness	0.047" (1.194mm)	
Material Type	Galvalume® AZ55	

Target Membrane

Manufacturer	FiberTite
Color	Off-White*
Length	11.75"
Width	11.75"
Thickness	50mil XT*

Packaging - Sold Individually or Full Box Quantity

Individual Weight	Approx. 0.75 lbs	
Full Box Quantity	10 units	
Box Weight	10 lbs	
Box Dimensions	13" x 11" x 13"	
Full Pallet Quantity	50 boxes	
Pallet Dimensions	48" x 40" x 67"	

^{*} Specified option is standard. Custom options may be available for additional charge. Custom lead times may apply depending on product availability.







Back View





For more information on FiberTite Systems and accessories please call: Seaman Corporation (800) 927-8578 International (330) 262-1111 www.FiberTite.com

FiberTite® is a registered trademark of Seaman Corporation. U-Anchor™ is a trademark of Anchor Products™