2020 PANDO 2.0 STANDARD FEATURES

Weights (lb) / Dimensions (in) / Capacities (gallons, cubic ft):

о -p (9 ,)
2200
300
3500
29°
21
89
166
79
120
76
46 1/8
80
56 5/8
14 (primary), 19 (optional secondary tank)
78.5 x 56.5
4 cabinets: 18x10x19 (8 cubic feet), spice rack: 18x20x10 (2 cubic feet)
15x12x56 (6 cubic feet), 15x14x56 (6 cubic feet)







FRAME (ANTISKID BLACK POWDER COATING)

- CNC Laser cut and formed 4-inch C-channel steel frame (3/16" side rails)
- Engineered laser cut supports for Timbren 3500HD axle less suspension
- 2" Front and rear receiver with standard 2" ball hitch
- 0.100" Aluminum removable two-piece fenders with 10g steel load bearing fender support
- Removeable rear bumper tail light guards
- Integrated mounting points for all frame mounted accessories including stabilizer jack option





SUSPENSION AND RUNNING GEAR

- Timbren 3500HD Axle less suspension with 12-inch electric brakes and battery back up breakaway system
- 265/65/R17 wheels paired with 6x5.5 bolt pattern off-road tires

CABIN

Composite Walls/Roof

- .090" aluminum outside skin (3M vinyl wrapped), 0.064" aluminum painted white inside skin, 1.5"x 1/8" aluminum tube subframe, CNC cut R10 rigid foam insulation
- One-piece wrap around roof and galley door to minimize water penetration

Composite Floor (above frame)

• 0.050" aluminum subfloor, CNC cut R10 rigid foam insulation, 5/8" composite Thermo-lite board (non-absorbent, mold/mildew resistant)

Cabin Features

- Custom OGT 23.75" x 42.75" lockable with tinted window/screen and sweep out threshold
- Accessible and removeable wire track for easy electrical wiring access
- 4 x USB ports, digital voltmeter display, interior LED lighting, dual 120V outlet with Go-Power remote
- Maxxfan 10 speed reversible roof fan
- Integrated anti skid powder coated side steps both sides
- Dual aluminum powder coated friction hinged storage cabinet doors with cabinet storage
- Custom manufactured upholstered and vinyl backed (zippered) 1.2lb 4-inch-high density memory foam mattress
- 14-gallon primary and optional 19-gallon secondary CSA approved potable fresh water tank, serviceable and accessible/removeable with 2.9 gallon/min pump



REAR GALLEY

- 1/8" aluminum CNC laser cut and formed galley configuration
- Lockable dual latched galley door
- Unique galley door featuring rollover design and hinge and door seal water channels to seal galley compartment
- 4 upper aluminum powder coated friction hinged storage cabinet doors with cabinet storage
- Single upper cabinet aluminum powder coated lockable slide out spice rack
- Stainless steel counter top surface
- Dometic stainless steel dual burner stove with ignition
- OGT custom stainless steel hot/cold deep sink with stainless steel strainer and fold down faucet
- Dometic 57L fridge freezer with removable freezer divider
- Lower cabinet pot and pan drawer with side access
- Galley door overhead LED lighting and dual USB outlets
- 11lb LP cylinder side mounted on aluminum lockable cylinder bracket





Tongue Box

- Removeable black powder coated shelf tray
- Dual bank (10A/bank) smart shore power charger, Zamp solar ready port, 1000W Go Power modified sine wave inverter, 50A 12 circuit main BUS, 7 PIN junction box
- Powder coated vented battery box with dual 12V Group 31 deep cycle batteries (130ah reserve)

SHOWER / HEATER BOX

 Eccotemp L5 hot water on demand with outside shower attachment



