



Stainless Steel Banding – TYPE 201

100 Ft. coil in self dispensing carton

Type 201 Stainless Steel .030" thick, 2B finish, annealed

Carton dimensions: 10 1/4" x 10 1/4" x 1 1/4"

Part	Width inches	Width mm	Weight/Ctn lbs	Weight/Ctn kg	Tensile Strength lbs
BNG2014	1/2	13	5.2	2.3	1710
BNG2015	5/8	16	6.4	2.9	1940
BNG2016	3/4	19	7.7	3.5	2290

Extra strong, type 201 stainless steel banding is suitable for general banding e.g., fasten signs, signals, control boxes and other fixtures to poles, columns, pillars or beams.

Tensioning tools: **MTC2400**, **BT2440**, **RTS240**

Buckles: **TT2004** (1/2"), **TT2005** (5/8"), **TT2006** (3/4")

Accessories: **FLB** – SS Flared Leg Mounting Bracket; **SLB** – SS Straight Leg Mounting Bracket

FEATURES	BENEFITS
Type 201 stainless steel	Extra strength for medium and heavy duty applications
Annealed	Tensions easily; resists breaking Safeguards workers and materials Corrosion resistant
De-burred edges Stainless steel	Withstands extreme temperatures Unaffected by UV radiation
Self dispensing carton	Long lasting, no maintenance required Non-flammable Does not absorb water Suitable for use in air handling spaces Compact, easy to carry, easy to use



STOP sign mounted to pole using type 201 stainless steel banding, stainless steel buckles and mounting brackets.



Traffic Signal mounted to utility pole using type 201 stainless steel banding and buckles.

SPECIFICATIONS

Typical mechanical characteristics:

Typical chemical composition %:

C - .08; Mn - 6.78; P - 0.31; S - .004; Si - .41; Cr - 16.25; Ni

- 4.01; Mo - .22; Cu - 1.57; Co - .087;

Ti - .008; N - .05; Al - .019; Nb - .03

Tensile Strength - 100,835 PSI; Yield 41,185 PSI;

Elongation 59%; Hardness 52 45T

Standards:

ASTM A240/A 240M 15a type 201 annealed

Origin: USA

Unit 6 -676, Monarch Ave, Ajax, ON L1S 4S2

905-428-3444

sales@frommpackaging.ca

www.frommpackaging.ca



Stainless Steel Tiger Teeth Buckles

TYPE 201 & 316

100 pieces per box

Box dimensions: 6 1/2" [165 mm] x 4 1/2" [115 mm] x 3 1/2" [90 mm]

Part #	Stainless Type	Banding Size	Width inches	Width mm	Thickness inches	Thickness mm	Weight/Box lbs	Weight/Box kg
TT2002	201	1/4	.3	7.7	.051	1.3	.6	.3
TT2003	201	3/8	.4	10.2	.051	1.3	.8	.4
TT2004	201	1/2	.6	15.3	.051	1.3	1.8	.8
TT2005	201	5/8	.8	20.5	.059	1.5	2.0	.9
TT2006	201	3/4	1.0	25.6	.070	1.8	3.4	1.5
TT3163	316	3/8	.4	10.2	.051	1.3	.8	.4
TT3164	316	1/2	.6	15.3	.051	1.3	1.8	.8
TT3165	316	5/8	.8	20.5	.059	1.5	2.0	.9
TT3166	316	3/4	1.0	25.6	.070	1.8	3.4	1.5

Type 201 stainless steel buckles are suitable for use in general banding applications. Type 316 stainless steel buckles are suitable for banding applications in marine and other corrosive environments.

Banding: BNG201X, BSB201X, BSB316X

Tensioning tools: MTC2400, BT2440, RTS240, RTS2230, LTC100 (3/8" & 1/4" only)

Accessories: FLB – SS Flared Leg Mounting Bracket

FEATURES	BENEFITS
Type 201 stainless steel Type 316 stainless steel	Extra strength For use in saline environments
De-burred edges	Safeguards workers and materials
Stainless steel	Withstands extreme temperatures Unaffected by UV radiation Long lasting, no maintenance required Non-flammable Does not absorb water Suitable for use in air handling spaces
Wide throat & high bridge	Slides easily over band, accommodates double band
Tiger Teeth	Firm grip, no slip



Steel Strapping – Econo Packs

200 Ft. (60 m) coil steel strapping in self dispensing carton


Regular Duty Steel Strapping - .020" (.5 mm) thick

Carton dimensions: 10.25" (260 mm) x 10.25" (260 mm) x 1.25" (32 mm)

Part	Width inches	Width mm	Weight/Box lbs	Weight/Box kg	Break Strength lbs	Description
10.9300-200	1/2	13	7.0	3.2	1180	Std duty
10.9380-200	5/8	16	8.5	3.85	1218	Std duty
10.9403-200	3/4	19	10.0	4.5	1255	Std duty
10.9403P-200	3/4	19	10.0	4.5	1255	Hole punched

Seals

PRODUCT	STRAP SIZE (inches)	SEAL LENGTH (inches)	THICKNESS (inches)	PIECES PER CASE
OST48	1/2"	1.25	.020	2500
OST58	5/8"	1.25	.020	2500
OST68	3/4"	1.25	.020	2500
OVERLAP SEALS (PUSH TYPE)				
PT48	1/2"	.875	.025	2500
PT58	5/8"	.875	.025	2500
PT68	3/4"	.875	.025	2500



FEATURES	BENEFITS
Regular Duty carbon steel	For light and medium duty applications
Black coating	Resists corrosion
De-burred edges	Safeguards workers and materials
Self dispensing box	Compact, easy to carry, easy to use Suitable for shop or truck No cart required Low cost – ideal for companies that ship small quantities, or those that ship infrequently, or for job sites



54116 - All Purpose Banding - 5/8"

All Purpose banding is galvanized steel banding with pre-punched holes. Use it for general bundling, fastening and hanging applications.

Description

5/8" (17mm) x .028" (.7mm) with 17/64" (7mm) diameter holes at 13/16" (20mm) centers
33 ft (10m) on self-dispensing spool – 6" dia. X 1", wt 1.6lbs

Sold per coil

To Fasten All Purpose Band

1. Fit the band around the objects to be fastened and form a loop.
2. Cut off.
3. Match holes in both sides of the loop at the desired position.
4. Insert max 1/4" (6mm) bolt(s) through the holes and tighten nuts to secure.



FEATURES	BENEFITS
Plastic Self Dispensing Spool	<ul style="list-style-type: none"> • Compact, convenient, durable, weather resistant, easy to carry and store • Low cost
Pre-punched banding	<ul style="list-style-type: none"> • No special tools required, fasten with bolts or screws
Galvanized steel	<ul style="list-style-type: none"> • Durable, long-lasting, no maintenance required • Corrosion Resistant • Non Flammable • Does not absorb water • Unaffected by UV Radiation • Withstands temperature extremes