



Certificate of Compliance

Certificate: 70186009

Master Contract: 251419

Project: 80019398

Date Issued: 2020-03-31

Issued To: Ortal Ltd
14 Haharash St.
Hod Hasharon, ., 45240
Israel

Attention: Tal Gross

The products listed below are eligible to bear the CSA Mark shown with adjacent indicators 'C' and 'US' for Canada and US or with adjacent indicator 'US' for US only or without either indicator for Canada only.

Issued by: Parker Burrola
Parker Burrola



PRODUCTS

CLASS 2915 01- FIREPLACES Vented (Gas)

CLASS 2915 81- FIREPLACES Vented (Gas) – Certified to U.S. Standards

Model Number

Maximum
Input Rating

Minimum
Input Rating

Altitude

For Use With Natural Gas
Gravity Vented Gas Fireplace, Recessed

Trade Name: Ortal, Lyric

Traditional 110 TS/RS/LS

55,000

9,000

N



Certificate: 70186009
Project: 80019398

Master Contract: 251419
Date Issued: 2020-03-31

| | | | |
|--|--------|--------|---|
| Traditional 110 | 55,000 | 9,000 | N |
| Traditional 90 TS/RS/LS | 55,000 | 9,000 | N |
| Traditional 90 | 55,000 | 9,000 | N |
| 7565H/TU | 55,000 | 9,000 | N |
| Stand Alone 65X75 Curve DG | 49,500 | 9,000 | N |
| Stand Alone 65X75 Curve TU DG | 49,500 | 9,000 | N |
| 75TSH | 49,500 | 9,000 | N |
| 75H/RS/LS DG | 49,500 | 9,000 | N |
| 110 DG | 49,500 | 9,000 | N |
| | | | |
| 160 Burner | | | |
| Clear – 200/H/RS/LS/TS/Tunnel | 51,277 | 36,659 | N |
| Space Creator 200 | 51,277 | 36,659 | N |
| Space Creator 200H | 51,277 | 36,659 | N |
| Clear - 250/RS/LS/TS/Tunnel | 51,277 | 36,659 | N |
| Clear – 250H RS/LS/TS/Tunnel | 51,277 | 36,659 | N |
| | | | |
| 180 Burner | | | |
| Clear – 200 RS/LS/TS/Tunnel/DG | 52,700 | 21,700 | N |
| Clear-200H RS/LS/TS/Tunnel | 52,700 | 21,700 | N |
| Space Creator 200 | 52,700 | 21,700 | N |
| Space Creator 200H | 52,700 | 21,700 | N |
| Clear - 250/RS/LS/TS/Tunnel/DG | 52,700 | 21,700 | N |
| Clear – 250H RS/LS/TS/Tunnel | 52,700 | 21,700 | N |
| | | | |
| For Use With Propane Gas | | | |
| Gravity Vented Gas Fireplace, Recessed | | | |
| | | | |
| Traditional 110 RS/LS/TS | 28,500 | 17,796 | N |
| Traditional 110 | 28,500 | 17,796 | N |
| Traditional 90 TS/RS/LS | 28,500 | 17,796 | N |
| Traditional 90 | 28,500 | 17,796 | N |
| 75X65H/TU | 28,500 | 17,796 | N |
| Stand Alone 65X75 Curve DG | 28,500 | 17,796 | N |
| Stand Alone 65X75 Curve TU DG | 28,500 | 17,796 | N |
| 75TSH | 28,500 | 17,796 | N |
| 75H/RS/LS | 28,500 | 17,796 | N |
| 110 DG | 28,500 | 17,796 | N |

***Altitude:** N = 0 to 2,000 feet;
 De-rated 4% for every 1000 ft. above 2,000 feet.

APPLICABLE REQUIREMENTS

ANSI Z21.50/CSA 2.22-2016

- Vented Decorative Gas Appliances



Supplement to Certificate of Compliance

Certificate: 70186009

Master Contract: 251419

The products listed, including the latest revision described below, are eligible to be marked in accordance with the referenced Certificate.

Product Certification History

| Project | Date | Description |
|----------------|-------------|---|
| 80019398 | 2020-03-31 | Update report to add Baoamac electrical lights system. |
| 80009733 | 2020-02-14 | Update CSA report #: 70186009: 1. Test the largest and smallest models for rate and combustion and check temperatures on the model with the highest BTU per cubic ft ratio if the orifice size increased. Propane and NG. 2. Test the 200HH for delayed ignition (explosion test). Add Lyric tradename and indoor/outdoor through the wall kits to both 70186009 and 2358468 reports |
| 000070186009 | 2018-06-05 | Continuation of 70159615 for review of missing documentation and to finalize certification |