

### SPECIFICATIONS

Capacity Max	42 l/s
Head Max	50m
Nominal Duty	30 l/s @ 25 mtrs
Self priming lift	5 mtrs
Pump Speed	2400 rpm
Inlet/outlet (mm)	4" x 4" (100mm)

### RECOMMENDED ENGINES

Make	Model
Yanmar	3TNV82
Caterpillar	C1.1
Deutz	F2L 2011

### STANDARD MEASUREMENTS

Length (mm)	2050
Width (mm)	1030
Height (mm)	1740
Dry Weight (kg) approx	XXX
Fuel Tank Capacity (L)	320

### STANDARD PACKAGE

- Camlock connections (STD)
- Lifting frame with lifting point
- Forklift accessible
- Integral fuel tank
- Large battery + battery tray
- STD SAE flywheel + coupling guard
- Lockable fuel cap
- Remko K21 controller
- Weather protection roof
- Engine protection STD


### OPTIONAL EXTRAS

- Remote start - stop
- Float or level control
- Battery isolator
- Lockable battery box
- Emergency stop
- Solar panel
- Flashing lights
- Fire extinguisher
- Skid base
- Trailer mounted




\*RT150 pump pictured

## BUILT TO BE TOUGH



**DESIGN:** Robust and heavy duty to meet the demands of the construction, agriculture, mining and rental industries.

**EFFICIENCIES:** Pump and motor efficiencies up to 80% which provides faster and more efficient pumping, resulting in savings to the user



Lifting Frame with Lifting Points

Emergency Stop (Optional Extra)

Weather Protection Roof

Heavy Duty Self Priming Pump (RT150 pump pictured)

Remko K21 Controller

Deutz Engine Standard (Options Available)

Integral Fuel Tank

Fire Extinguisher (Optional Extra)

Heavy Galvanised Frame Forklift Accessible

## FEATURES & BENEFITS

- Complete Turn Key Package
- Galvanised Finish
- Centre Point Lift
- Forklift Accessible
- Built Tough
- Custom Build Available
- Various Pump/Motor Options



Remko irrigation pump packages are built to a high quality standard with affordability in mind

With the irrigation and civil market, there are multiple applications - We will help select the best pump, motor, and package combination to suit your specific applications

## REMKO K21 CONTROLLER



- Low Oil Pressure Shutdown
- High Coolant Temp Shutdown
- RPM Display (Overspeed Shutdown)
- 100 Hour Run Timer
- Engine Hour Meter
- Battery Voltage Monitor/Display
- Low Radiator Level Shutdown
- 4-20mA Pump Pressure

Remko