

REMKO RT200
Heavy Duty Trash Pump

Remko



REMKO RT200

Self priming with dependable performance makes RT Series Pumps a sensible solution for industry and municipalities requiring little maintenance, resulting in significant savings of time and money.

RT Series Pumps are ideally suited for industrial applications including: steel and paper mills, abattoirs, mines, food and chemical processing plants, construction industry, dewatering, trade waste and sewage handling.



The Remko RT200 Trash Pump

PUMP SPECIFICATIONS

SPECIFICATIONS

Maximum outside dimensions. 1024mm x 705mm x 1069mm (length x width x height)

Weight. 594 kilograms

Impeller diameter. 374.65 millimetres

RPM. From 650 to 1350 RPM

Solids. 76 millimetres maximum

SELF PRIMING SPECIFICATIONS

650 RPM - 2.7 metres. 750 RPM - 3.7 metres. 850 RPM - 4.6 metres. 950 RPM - 5.2 metres.


1050 RPM - 6.1 metres. 1150 RPM - 6.4 metres. 1250 RPM - 6.7 metres. 1350 RPM - 7.0 metres.

Confirm NPSH before using Curve.

Note: Specifications may change without notice

PERFORMANCE CURVE

The Performance Curve indicates Total Metres Head vs Flow Rate





OUTSIDE DIMENSIONS RT200

200mm ANSI 150

Pump dimensions may change without notice
All dimensions in millimetres

Ø 22.4mm





Contact your local Remko Distributor

Remko 1800 333 424