


## ASSEMBLY, 2 PORT PISTON, 55mm




The 2-port linear piston is a new item available from Penske Racing Shocks. The theory behind this piston stems from optimizing shim deflection efficiency by promoting a more natural bending moment. To this end, new clamping plates were devised to provide a straight line bending pivot surface and the piston received a non-traditional dish on its surface. To receive the largest benefit of this new arrangement, multiple base shims (1.475 O.D.) are recommended to run against the piston and directly against the new clamping plate. The piston has a 5/8" nominal inner diameter so that it may be run with the digressive blow-off cage and the new decoupled top-out plate. The piston is machined from the same thermally stable aluminum alloy as the current linear and high-flow pistons and accepts the standard piston band and o-ring as the other Penske pistons.

AS-2PORT55......230.00 each

Assembly, 2 Port Piston, 55mm



Blowoff 2 Port, Graph #1 (located on back)



Linear 2 Port, Graph #2 (located on back)

## The Competitive Advantage of Champions

Main Office 150 Franklin Street P.O. Box 1056 Reading, PA 19602 Phone (610) 375-6180 Fax (610) 375-6190 PRS Midwest 12666 U.S. Route 12 P.O. Box 666 Brooklyn, MI 49230 Phone (517) 592-6681 Fax (517) 592-3696 PRS Southeast 771-28 Fentress Boulevard P.O. Box 11586 Daytona Beach, FL 32114 Phone (386) 274-5332 Fax (386) 274-5442 PRS Canada 360 York Road, RR #4 Niagara on the Lake N.O.T.L., Ont., LOS 1J0 Phone (905) 684-7418 Fax (905) 684-1774

