

RSX-8

The RSX-8 is a miniature low profile AT-cut quartz crystal. True SMD style, ceramic package with nickel plated lid, seam welded. The product is supplied on tape and reel.

Features

- Low ageing
- Wide frequency and temperature ranges

Applications

- Automotive and GNSS
- Handset, PND, and PDA
- Communications
- Feature phone

3.2 x 2.5 x 0.7 mm



Standard Specifications

Parameter	Min.	Typ.	Max.	Unit	Test Condition / Description
Nominal frequency		10 - 125		MHz	
Calibration tolerance			±10 to ±50	ppm	Frequency at 25°C ± 2°C and specified load capacitance
Reflow shift			±1	ppm	Frequency shift after reflow with 4 hours settling at 25°C
Temperature range	-40		85	°C	Operating temperature
Frequency stability over temperature			±10 to ±50	ppm	Referenced to frequency reading at 25°C and the specified load capacitance
Frequency perturbations			1	ppm	Residual error from the frequency versus temperature curve fit 5th order. Minimum of 1 frequency reading every 3°C over the operating temperature range
Long term stability			±1	ppm	Frequency drift over 1 year at 25°C
g sensitivity			2	ppb/g	Gamma vector of all three axes from 30 Hz to 1500 Hz
Load capacitance (CL)		5 to 32		pF	Frequency is calibrated at room temperature
Shunt capacitance (CO)		0.5 to 3		pF	
Drive level			50	µW	
Equivalent series resistance (ESR)			60	Ω	
Insulation resistance (IR)	500			MΩ	100 V ±15 V at 25°C

Model Outline and Recommended Pad Layout

